

General Description

3107 is a premium clear, high gloss penetrating type concrete, masonry and other interior surfaces sealer based on specially formulated aqueous acrylic –urethane combination that will not yellow with exterior exposure. This coating is outstanding in its ability to protect surfaces from chemicals, staining and discoloration. Diamond Sheen has been tested and approved by Canada Food Inspection Agency for use in food sensitive areas.

Uses

Interior - Protective coating for concrete and other substrates against occasional spills of acids, alkalis, food acids, oil, water based paints, wet concrete, etc. Minimal odor while wet.

3107 displays a unique balance of hardness, flexibility and impact resistance.

Physical Properties

Appearance	-	Milky white liquid – dries clear
Density (25°C)	-	1.02 kg/litre (8.74 lb/U.S. gallon)
Dry Film Appearance	-	Clear
Drying Time (21°C)	-	1 - 2 hours
Coverage	-	200 - 330 square feet per U.S. gallon
Solids	-	30%
V.O.C.	-	95 grams/ Litre

Application Instructions

Make sure surface is free of oil and dirt. This can be achieved by scrubbing with a soap solution of trisodium phosphate (TSP) or a mild acid solution. After cleaning, rinse the surface thoroughly and let dry. Apply IM 3107 by spray, brush or roller. Apply above 10°C (50°F). Substrate must be free of moisture. New concrete must have cured for 14 days.

Clean Up

Tools can be cleaned up with water after use.

Packaging

Available in 4 litre (1 gallon), 20 litre (5 gallon), and 205 litre (55 gallon) containers.