

1 of 2 pages

## Product Description

Innovative Mfg. Acrylic Stains are designed to provide an economical and efficient method of colouring both horizontal and vertical concrete and masonry surfaces. Formulated with specially refined pigments, Innovative Mfg. Acrylic Stains create a transparent colouration of the surface allowing the natural textures of concrete and masonry to continue.

## Uses

Innovative Mfg. Acrylic Stains can be used on new or existing concrete and masonry surfaces as a transparent, decorative finish. When used in conjunction with stenciling techniques, unlimited designs can be achieved. Innovative Acrylic Stains are ideally used in areas where a colour system that permits the texture of the concrete and masonry to continue is wanted.

## Yield

- Available in several standard colours – refer to Innovative Mfg. Colour Selector Chart
- Available in custom colours upon request
- First Coat: 200-350 ft<sup>2</sup>/gallon (4.92-8.60 m<sup>2</sup>/litre)
- Second Coat: 300-450 ft<sup>2</sup>/gallon (7.37-11.06 m<sup>2</sup>/litre)

Water based (V.O.C. 23.5g/Litre)

## Packaging

Available in 1 Gallon (3.78 litre) or 5 Gallon (18.9 litre) units

## Procedure

1. Surface should be clean and free from all foreign matter including any coating, waxes or adhesives.
2. Complete small test area using the material selected for approval prior to installation
3. Apply Innovative Mfg. Acrylic Stain using an airless sprayer in 2-3' bands with a circular motion to eliminate overlap lines.
4. Allow first coat to dry before re-application.
5. Apply a second, lighter coat to the surface.
6. After application of Innovative Mfg. Acrylic Stain, allow the surface to dry for a 24-hour period. Apply a wax emulsion as a protective coating by mop or sprayer. Re-apply the wax coatings every 3-6 months to protect the Acrylic Stain from excessive wear from traffic.
7. Allow the surface to dry completely prior to opening to traffic.

2 of 2 pages

## Limitations

1. Ensure all surfaces are clean and free from sealers, waxes, adhesives and other foreign material.
2. Scrub existing surfaces with an industrial scrubber.
3. Lightly mop the surface immediately prior to application with clean tap water.
4. Innovative Mfg. Acrylic Stain is not a wearing surface and must be protected from excessive traffic using an acrylic wax emulsion.
5. Innovative Mfg. Acrylic Stain is not intended for surfaces subject to heavy mechanical loads or vehicular traffic.
6. The use of curing compounds can affect the bond of Innovative Mfg. Acrylic Stains. Do not use curing compounds. Moisture cure concrete surfaces to be applied with Innovative Mfg. Acrylic Stains.
7. Do not use in areas where solvents may come in contact with the stain.

## Safety Precautions

Keep out of the reach of children. See Material Safety Data Sheet.

Store in a cool area. Do not allow direct sunlight for prolonged periods.

## Warranty

As the manufacturer does not have any control of the application process and conditions, liability is limited to the replacement of proven defective product.