

General Description

A flexible fibered non-shrinking sealer formulated from a solvent solution of natural asphalt.

Uses

A sealer for inside and outside duct work, plenums and other sheet metal equipment. Also, used as a sewer pipe joint sealing compound.

Limitations

It cannot be applied on damp or frosty surfaces. Openings to be sealed should not exceed 3mm (1/8 inch). Designed to withstand 38 cm (15 inches) of water static pressure.

Physical Properties

Colour	- Black
Drying time, tack free	- 8 hours at 21 ^o C
Coverage	- 17 meters per litre (210 linear feet per U.S. gallon)
Temperature Resistance	- -40 to 120 ^o C (-40 to 250 ^o F)
Flame Spread Index	- Int. Fed. Spec. #001368 - 30
Permeability	- .018 perms per .3cm
Flash Point	- 44 ^o C (110 ^o F)
Density	- 1.08 kg/l (9 lb/ US gal)

Preparatory Work

Surfaces must be free of frost and oil.

Precautions

This product is flammable and must be kept away from open flames. There is a strong solvent odour so ventilation is important. Harmful if swallowed.

Work Characteristics

15191 will not freeze, but warming is necessary in cold weather to reduce viscosity.

Installation Instructions

Applied with a brush, trowel or spray to give a uniform coating to the surface. Mineral Spirits can be used for clean up.