

Product Description

3110 Concrete Floor Finish (CFF) is a durable, protective topcoat designed to protect and enhance sealed interior concrete surfaces. 3110 Finish produces a premium high gloss appearance, while improving the stain resistance of interior coloured, or non-coloured concrete floors. This advanced formulation is easy to apply, and can be buffed to increase gloss, and restore appearance. 3110 is ideal to help reduce the slipperiness of smooth interior concrete type floors.

Uses

CFF is ideal for commercial and residential applications that are exposed to incidental spills of industrial solutions, household cleaners and food products. 3110 can be applied to power troweled, polished or decorative, and other concrete style interior floors. CFF is economical to use and great for floors requiring ongoing maintenance programs.

Advantages

- Excellent durability
- Long term gloss retention
- Treated floors maintain slip resistance
- Easy to re-apply, great re-coat ability
- Improves stain resistance
- Makes cleaning and maintenance faster
- Scuffs and abrasions can be polished out
- VOC Compliant
- Non-toxic

Application Instructions

Make sure surface is free of foreign matter including dust, debris, grease and oil, curing compounds or bond breakers. Test in an inconspicuous area to insure product performance, satisfaction, as well as required coverage.

Estimated Coverage: 400 – 2000ft²/gallon depending on surface texture
10 – 38 m²/L depending on surface texture

Apply CFF in thin even coats, with a paint pad, synthetic or lambs wool applicator.

Two thin coats are recommended for maximum protection*

Allow 30-60 mins between coats.

If a higher gloss is desired wait a minimum of 2 hours after the final coat, then use a white polishing pad mounted on a high speed burnishing machine. Work the burnishing machine at a fast walking pace.

*Standard number of coats is 2-3, never exceed 5 coats in 24hrs.

Limitations

Take care to apply in a very thin film. The use of paint rollers is not recommended for application.

On new installation, a second coat is recommended.

CFF will repel stains more effectively and clean more easily when proper cleaning solutions and methods are used.

Product Maintenance

Dust mop and clean the area regularly to remove abrasive debris. Use a damp mop with a neutral pH solution to remove any spills or debris missed by dry mop.

Periodically inspect floor finish for thin or traffic worn areas.

To refresh faded gloss in an area, use white polishing pad and dry buff with high speed burnishing machine to restore the gloss.

High traffic areas may require re-application, follow applications instructions.

Re-apply CFF as needed.

CFF can be applied multiple times before stripping is required.

To remove CFF use Innovative Floor Finish Remover as directed.