

## General Description

Kwik Prime is a quick dry, solvent based, rubber primer designed for use with self adhering membranes.

## Uses

Used as a primer for self adhering membranes on such substrates as concrete, masonry, wood, gypsum, water repellent gypsum and sheet metals.

## Limitations

Not to be used on polystyrene insulations or in areas where solvent odors may taint food or other susceptible products.

## Physical Properties

Colour	-	Hazy orange
Specific Gravity	-	0.78
Dry to Touch	-	30 min. pail applied, 3 min. spray can applied.
Dry to Firm	-	2 hours pail applied, 20 min. spray can applied.
Application Temperature	-	-12 to 40 deg C
Coverage ( depending on porosity of surface.)	-	Up to 250 sq. ft. per U.S. gallon pail applied. 25 to 45 sq. ft per can.
Flammability	-	Wet – Flammable Dry- Burns

## Preparatory Work

Surfaces must be clean, dry and free from dust, dirt, grease and oil.

## Precautions

Contains extremely flammable solvents. Maintain good ventilation and keep away from sparks or open flame. Avoid prolonged breathing of vapours and repeated skin contact. Use respirator approved for organic vapours. Keep pails covered when not in use. Harmful if ingested.

## Installation

Apply by brush, roller, or spray equipment at the specified rate. Primed surfaces not adhered to with membrane within same workday should be reprimed. Spray cans should be shaken before use. Clean up with Xylene.