

## General Description

7501 Fast Dry Primer is a fast drying thin, solvent-reduced, penetrating primer for sealing and revitalizing dried-out, absorbent surfaces before applying asphaltic coatings. Fast Dry Primer penetrates porous surfaces and quickly sets to ensure an excellent substrate bond for membranes and coatings. Meets current revisions of CGSB-37-GP-9M.

## Uses

Its main use is for priming absorbent surfaces to improve the bond and provide a tack coat for the application of modified asphalt coatings or sheet membranes.

## Limitations

This is a flammable product and care must be taken to keep away from open flames and provide ventilation to remove fumes. It should not be stored at temperatures in excess of 50°C or 120°F.

## Physical Properties

Colour	-	Black
Solids	-	55 % minimum
Drying Time	-	Touch dry – 30 min. at 25°C (77°F) Firm dry – 2 hours at 25°C (77°F)
Density	-	0.90 kg per litre (7.5 lb per U.S. gallon)

## Preparation

Surfaces should be clean, dry and scraped clean of gravel dirt and rough projections.

## Characteristics

It is a thin solution and will not freeze. It is applied at a rate of 2.4 to 3.7 litres per 10 square meters (1/2 to 1 gallon per 100 square feet).

## Application

Roofs - Apply by brush, roller, spray at a rate of 1/4 to 1 litre per square meter (½ - 2 gal/100 sq.ft.). Use adequate amount without pooling. Let primer dry before applying asphalt topcoat.  
Foundations - Apply by brush, roller or spray at a minimum rate of 0.4 litres per square meter (1gal/100sq.ft.). 510 gram Spray Primer coverage approx.24 sq.ft per can.