

## General Description

A brush or spray consistency bituminous paint with gilsonite additives which dries to a glossy, tack-free finish. Has good chemical resistance.

## Uses

An economical coating for the protection of metal from atmospheric or underground chemical attack. EXCELLENT alkali barrier between aluminum and concrete or masonry surfaces. It is used as a coating on metal roofing, gutters and services.

## Limitations

When used as a primer under asphalt emulsion coatings and finishes allow to cure for 12 hours before application of the coating. Dry film will redissolve in petroleum solvents. On exposed weathering it will chalk and lose gloss.

## Physical Properties

Colour	-	Black
Density	-	0.9 kg per litre (7.6 lb. per U.S. gallon)
Coverage	-	2 to 6 square meters per litre (80 – 245 sq. ft. per gallon)
Dry Time	-	at 50%R.H.and 21 <sup>o</sup> C
Dry to Touch	-	1 hour
Dry to Firm	-	4 hours
Service Temperature	-	-35 to 82 <sup>o</sup> C (-30 to 180 <sup>o</sup> F)
Shelf Life	-	Up to 12 months

## Precautions

Contains flammable solvents. Take suitable fire precautions. Harmful if swallowed

## Application

Apply by brush, spray or roller. Two coats are recommended for improved chemical resistance.