

General Description

All Weather Roof Patch is a solvent based rubberized asphalt patching compound. It contains mineral fibers and fillers and can be brushed at 7°C (20°F) or warmer. Roof Patch adheres to wet or dry surfaces making it ideal for emergency repairs.

Uses

7514 is designed to be used in adverse conditions, as an all weather patching compound for repairing roofs, flashings, vents, skylights and shingles. All Weather Roof Patch remains tacky for a relatively long time to enable it to melt into a repair situation.

Limitations

Where large areas are to be coated or where faster drying is required either 7504 or 7509 should be used.

Physical Properties

Colour	- Black
Drying Time	- Remains soft for an extended period
Density	- 1.12 kg per litre (9.3 lbs. per gallon)
Shelf Life	- Up to 12months

Preparatory Work

Mix before using. Clean dirt, ice, snow and excess water off surface before application.

Precautions

Contains flammable solvents. Take suitable fire precautions. Harmful if swallowed.

Work Characteristics

Apply with a short, stiff bristle brush. Do not over brush as roof patch fibers tend to be dragged by the brush.

Application

Cracks up to 7mm (1/4") deep should be filled with Roof Patch then top coated with a 3 mm (1/8") coating that extends well beyond the crack in all directions.

Deep cracks should be filled, and allowed to cure for an hour before top coating. To repair very large cracks or holes, embed 20/10 Glass Cloth under top coat.