

1 of 2 Pages

**General Information**

ECO-STRIP STRIPPER is a 100% biodegradable, VOC compliant coating stripper, containing no hazardous ingredients. It is a safe and effective product to remove paint, and coatings from various substrates.

It is a safe and effective product to remove paint.

**Features:**

- 100 % Biodegradable (all natural ingredients)
- Environmentally friendly
- Non toxic
- Contain no cancer-causing methylene chloride (DCM), or caustic alkalis (burning of skin and eyes)

**Uses**

- Removes concrete sealers
- Removes oil-based, and latex paints
- Removes lead-based paints
- Removes varnishes
- Removes two part epoxies
- Removes urethane paints
- Effective on many surfaces, including wood, metal, concrete, glass, aluminum sidings, tile, brick, furniture, equipment, and more.
- ECO-STRIP STRIPPER may be used on vertical as well as horizontal surfaces indoors and outdoors.

**Limitations**

Do not use on plastic, PVC, rubber or dry wall.

PROTECT FROM FREEZING

**Product Information****COMPOSITION AND MANUFACTURE :**

ECO-STRIP STRIPPER is an organically-derived solvents product.

Its very low evaporation rate enables the removal of several layers of paint.

**PHYSICAL DATA:**

Appearance	White viscous liquid
Specific Gravity	0.95
pH	7-8
Odor:	Mild odor

ECO-STRIP STRIPPER is packaged in 1 liter, 3.78 liters, 18.9 liters and 205 liter drum.



# 3414 ECO-STRIP STRIPPER

861 Derwent Way, Delta, BC, Canada V3M 5R4  
Telephone 604 -522 -2811 Facsimile 604 522-5141

## PRODUCT BULLETIN

Page 2 of 2

### First Aid

Avoid eye contact. Use eye protection equipment. Flash eyes with running water for at least 30 minutes. Obtain medical attention. Do not induce vomiting if swallowed. Drink large amount of water. Immediately call a physician.

For skin contact, wash with soap and water. Remove contaminated clothing, and if irritation persists call a physician.

### Application Instructions

1. ECO-STRIP STRIPPER is ready to use and can be applied by brush, roller or airless sprayer.
2. Type of coating and number of layers will determine the amount of time needed for ECO-STRIP to work.
3. Check the progress of the stripping action with a scraper to see if the coating has softened or lifted from the surface. If not lifted, allow to sit for 10 minutes and recheck as necessary.
4. Once the coating is lifted from surface (time required for most coatings is 20-30 minutes) remove it with a scraper, a stripping tool, deck brush, or rinse off with cold medium-high pressure water.
5. Some polyurethane coatings require 1-2 hours stripping time.

### Rate of Application

#### **COVERAGE:**

- a. Horizontal surfaces- 200 sq. per 3.78 litres.
- b. Vertical surfaces- 140 sq. ft. per 3.78 litres.

### Warranty

INNOVATIVE MFG. strives to manufacture the highest quality products using selected raw materials, manufacturing methods and testing procedures. INSULMASTIC products are warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over the end use of the product, no warranty, expressed or implied, is made to effects of such use. Sellers and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.