

Product Description

Resolve is a blend of specially selected solvents for re-dissolving and rejuvenating Innovative Mfg. solvent based acrylic sealers.

Uses

Resolve is used for removing whitening problems related to excess moisture trapped under the sealer surface. Whitening is typically a result of either too much moisture in or on the concrete prior to sealer application or the sealer was applied when substrate temperature is above 20 C°, preventing an adequate bond. Resolve works by re-dissolving (melting) the acrylic resin and allows it to re-bond to the surface. Resolve works to clear up the cloudy white areas, and restores the gloss of the remaining sealer.

Application

Generously apply Resolve over affected area with roller or sprayer. Make sure enough product is used to rejuvenate the resin. As Resolve begins to work the white area darkens as the resin is melted. Allow Resolve to evaporate, and apply a new coat of sealer if needed. If the above method does not work it could mean there is an over accumulation of sealer on the surface. If this is the case proceed as follows. Pour Resolve onto affected area. Using a clean solvent resistant scrub brush scrub area and allow Resolve to evaporate. Care must be taken not to overwork the resin and allow the sealer to ball up on the brush or be dragged across the surface. Apply a new coat of acrylic sealer to area as needed.

Limitations

Use only on solvent based acrylic sealers. Do not use on vinyl siding or plastics.

Caution

Flammable. Harmful or fatal if swallowed. Vapour harmful. Use personal protection (solvent resistant gloves, glasses and an approved respirator). Use under well ventilated conditions. Keep away from open flame or spark.

First Aid Treatment

If swallowed, call physician or Poison Control Centre immediately. Contains Xylene.